

TERMINATIONS

DC to 20 GHz



MODEL PREFIX	FREQUENCY RANGE (MHz)	RETURN LOSS, dB (MHz) Min.								POWER RATING (W)	CONNECTOR
		DC-1000	DC-2000	DC-4000	DC-6000	DC-8000	DC-12000	DC-18000	DC-20000		
50 Ω											
BTRM-50	DC-2000	30	21	—	—	—	—	—	—	0.5	Male-BNC
LOUIS-50	DC-2000	28	21	—	—	—	—	—	—	0.125	DIN Male w/retaining sleeve
KARN-50	DC-8000	30	29	27	—	20	—	—	—	2.0	Male-TYPE N
KARN-50CN	DC-8000	30	29	27	—	20	—	—	—	2.0	Male-TYPE N
KARN-50-18	DC-18000	35	30	30	—	26	20	18	—	2.0	Male-TYPE N
ROSE-50	DC-6000	33	30	23	20	—	—	—	—	0.5	SMB-PLUG
ANNE-50	DC-18000	30	30	30	27	27	23	21	—	1.0	Male-SMA
ANNE-50CN	DC-18000	30	30	30	28	28	26	20	—	1.0	Male-SMA
ANNE-50L	DC-12000	26	26	26	21	21	18	—	—	1.0	Male-SMA
ANNE-50X	DC-20000	30	30	30	30	30	30	26	20	1.0	Male-SMA
75 Ω											
BTRM-75	DC-1000	20	—	—	—	—	—	—	—	0.5	Male-BNC, 75Ω